Ref #	Hits	Search Query	DBs	Default Operator	Plurals	Time Stamp
L1	2631	((retriev$3 or request$3) with (file$1 or object$1)) same decod$3	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2005/05/05 16:16
L2	2758	((retriev$3 or request$3) with (file$1 or object$1 or xml or html or sgml or sxlt)) same decod$3	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2005/05/05 16:26
L3	47	2 and gopher	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2005/05/05 16:21
L4	16	3 and "707"/$.ccls.	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2005/05/05 16:21
L5	0	((retriev$3 or request$3) with (file$1 or object$1 or xml or html or sgml or sxlt)) same decod$3 same gopher	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2005/05/05 16:27
L6	0	(decod$3 with (retriev$2 near2 object$1)) same (gopher or http)	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2005/05/05 16:29
L7	47	(decod$3 with (retriev$2 near2 object$1))	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2005/05/05 16:44
L8	1	(decod$3 with (retriev$2 near2 (object$1 or xml or html or sxlt))) same (gopher or ftp)	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2005/05/05 16:32
L9	4	((decod$3 or conver$6) with (retriev$2 near2 (object$1 or xml or html or sxlt))) same (gopher or ftp)	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2005/05/05 16:33
L10	0	((decod$3 with (retriev$2 near2 object$1)) same xml) and gopher	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2005/05/05 16:45

L11	0	(decod$3 with (retriev$2 near2 object$1)) and gopher	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2005/05/05 16:45
L12	0	(decod$3 with ((retriev$2 or select$2) near2 (object$1 or xml))) and gopher	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2005/05/05 16:46
L13	215	(decod$3 with ((retriev$2 or select$2) near2 (object$1 or xml)))	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2005/05/05 16:46
L14	0	13 and gopher	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2005/05/05 16:46

(retrieval no program)